





# Soft Plastics





■ Upcut Spiral O Flute



<u>Soft Plastic</u>: ABS, Polycarbonate, Polyethylene, PVC, Polypropylene, HDPE, Polystyrene, UHMW, Foam, and Extruded Acrylic

Foam

High helix geometry designed to cut soft plastic with a smooth finish and upward chip flow. Special point geometry for improved bottom finish.



■ Double Edge

■ Solid Carbide

■ Downcut Spiral O Flute



<u>Soft Plastic</u>: ABS, Polycarbonate, Polyethylene, PVC, Polypropylene, HDPE, Polystyrene, UHMW, and

Extruded Acrylic Solid Surface

Designed to cut plastic with a smooth finish and downward chip flow.



Catalog Number	Cutting Edge Dia.	Cutting Edge Length	Shank Dia.	Overall Length
Inch				
H25XAM-46313	1/4	3/4	1/4	2-1/2
H25XOS-52-701	3/8	1-1/2	3/8	
H25XOS-52-702		1-1/4		4
H25XOS-52-704	1/2	1-3/4	1/2	4
H25XOS-52-706		2-1/8		
Metric	mm			
H25XOS-52-742		35		
H25XOS-52-744	12	45	12	100
H25XOS-52-746		55		

Helix Angle ≈22°

Catalog Number	Cutting Edge Dia.	Cutting Edge Length	Shank Dia.	Overall Length
Inch				
H25XOS-57-623	1/4	3/8	1/4	2-1/2
H25XAM-46413	1/4	3/4	1/4	2-1/2
H25XOS-57-637	3/8	1	3/8	3
H25XOS-57-651	1/2	1-1/8	1/2	3-1/2
Metric	mm			
H25XOS-57-627	6		6	64
H25XOS-57-639	8	25	8	76
H25XOS-57-643	10		10	70
H25XOS-57-645	12	35	12	88

Helix Angle ≈10-11°





## Soft Plastics





■ Straight O Flute

#### For Use On:

Soft Plastic: Acrylic, Melamine, Nylon, Polycarbonate, ABS, PE, Acetal, PET, HDPE and UHMW

Designed with free cutting O flute geometry along with a double flute design for smooth finish.







Designed with free cutting O flute geometry along with a double flute for improved part finish. The straight flute design helps to reduce part lifting in thin sheet applications.

### ■ Double Edge

- Solid Carbide
- Straight O Flute





### For Use On:

Soft Plastic: ABS, Polycarbonate, Polyethylene, PVC, Polypropylene, HDPE, Polystyrene, UHMW, and Extruded Acrylic



### METRIC

Catalog Number	Cutting Edge Dia. mm	Cutting Edge Length mm	Shank Dia. mm	Overall Length mm
H25XOS-56-430	4	16		
H25XOS-56-431	5	20	6	64
H25XOS-56-432	6	25		
H25XOS-56-434	8	25	8	76
H25XOS-56-436	10	35	10	88
H25XOS-56-438	12	35	12	00

Catalog Number	Cutting Edge Dia.	Cutting Edge Length	Shank Dia.	Overall Length
H25XOS-56-610	1/8	5/16		
H25XAM-43600	1/6	1/2		2
H25XAM-43604	3/16	5/8	1/4	
H25XOS-56-624		3/8	1/4	2-1/2
H25XAM-43608	1/4	1		2-1/2
H25XOS-56-628		1-1/4		4
H25XAM-43612	3/8	1	3/8	2-1/2
H25XAM-43616	1/2		1/2	3
H25XOS-56-655	1/2	2-1/8	1/2	6

Phone: 516-328-3970



# Soft Plastics

- Single Edge
- Solid Carbide
- Downcut Spiral O Flute

For Use On:

<u>Soft Plastic</u>: ABS, Polycarbonate, Polyethylene, PVC, Polypropylene, HDPE, Polystyrene, UHMW, and

Extruded Acrylic Solid Surface

Designed to provide a smooth finish in soft plastic with downward chip removal.





### METRIC

Catalog Number	Cutting Edge Dia.	Cutting Edge Length	Shank Dia.	Overall Length
H25XAM-51510	1/8	1/2	1/8	
H25XOS-62-762	1/6	1/2	1/4	2
H25XAM-51512	3/16	5/8	3/16	
H25XAM-51504	1/1	3/4	1/4	3
H25XOS-62-777	1/4	1-1/2		
H25XOS-62-783	3/8	1-1/8	3/8	3
H25XOS-62-790	1/2	1-5/8	1/2	3-1/2

Helix Angle ≈21°

			IVI	LIKIO
Catalog Number	Cutting Edge Dia. mm	Cutting Edge Length mm	Shank Dia. mm	Overall Length mm
H25XOS-62-852			2	50
H25XOS-62-854	2		6	64
H25XOS-62-856	2.5	8	2.5	50
H25XOS-62-858	2.5	0	6	64
H25XOS-62-860			3	50
H25XOS-62-862	3		6	
H25XOS-62-864	] 3	12	3	
H25XOS-62-866		12	6	
H25XOS-62-868		8	4	
H25XOS-62-870	4	12		
H25XOS-62-872		20		
H25XOS-62-874			6	64
H25XOS-62-876		30	4	04
H25XOS-62-878		16	5	
H25XOS-62-880	5		6	
H25XOS-62-882		30	5	
H25XOS-62-884		8	6	
H25XOS-62-886	_	12		
H25XOS-62-888	6	20		
H25XOS-62-890		30		76
H25XOS-62-892		38		
H25XOS-62-894	8	25	8	64
H25XOS-62-896		38		
H25XOS-62-898	10	30	10	76
H25XOS-62-899		35		
H25XOS-62-897	12	38	12	

Helix Angle ≈21°




## Soft Plastics




- Solid Carbide
- Straight O Flute

#### For Use On:

<u>Soft Plastic</u>: ABS, Polycarbonate, Polyethylene, PVC, Polypropylene, HDPE, Polystyrene, UHMW, and Extruded Acrylic





Catalog Number	Cutting Edge Dia.	Cutting Edge Length	Shank Dia.	Overall Length
H25XAM-43500		1/2	1/4	2
H25XOS-61-045	1/8	5/8	1/8	3
H25XOS-61-043			1/4	4
H25XOS-61-064	3/16		3/16	2-1/2
H25XAM-43504				2
H25XOS-61-081		3/8	1/4	2-1/2
H25XAM-43508	1/4	3/4	1/4	2-1/2
H25XOS-61-084*		1-1/4		4
H25XOS-61-121	3/8	5/8	3/8	2-1/2
H25XAM-43156	3/6	1	3/6	2-1/2
H25XAM-43520	1/2		1/2	3

Helix Angle ≈22°

### ■ Single Edge

- Solid Carbide
- Downcut Spiral O Flute

#### For Use On:

<u>Soft Plastic</u>: ABS, Polycarbonate, Polyethylene,PVC, Polypropylene, HDPE, Polystyrene, UHMW, and Extruded Acrylic

**Solid Surface** 

The polished flute allows for razor sharp cutting edge and easy chip evacuation. The down cut spiral helps improve part holding.





Catalog Number	Cutting Edge Dia.	Cutting Edge Length	Shank Dia.	Overall Length
H25XOS-64-000	1/16	1/4	1/8	
H25XOS-64-012	1/8	1/2	1/4	
H25XOS-64-016	3/16	3/8	3/16	2
H25XOS-64-018	3/10	5/8		_
H25XOS-64-024		3/8	1/4	
H25XOS-64-025	1/4	3/4	1/4	
H25XOS-64-026		1-1/4		
H25XOS-64-031	3/8	3/4	3/8	3
H25XOS-64-033	3/0	1-1/8	3/0	

Phone: 516-328-3970

Helix Angle ≈21°

<sup>\*</sup>This tool is designed and toleranced for air routers with guide bushings.